

End Of Line Units & Junction Boxes

End Of Line (EOL) units are used in conjunction with the Interface modules to terminate the Linear Heat Detection (LHD) cable and contain the appropriate EOL component or device. This allows the modules to monitor the LHD for any open circuit fault conditions.

Units fitted with test switches allow the alarm system to be tested for Fire and Fault conditions without the need for destructive use of any LHD.

The units are available in a number of different materials to suit different applications and environments.

**Pt Number End Of Line (EOL) units for
Digital Location Interface (DLI) and
Digital Interface Module (DIM-28).**


53106-001 Polycarbonate (PC) EOL unit.
Suitable for most applications. Supplied with
1 x PG 7 cable gland. IP66,
Dimensions 120 x 80 x 57 mm



53106-003 316 Stainless Steel EOL unit.
Suitable for harsh environments. Supplied
with 1 x M12 stainless steel cable gland.
IP 65. Dimensions 126 x 126 x 80 mm.



**53106-012 Aluminium EOL unit with internal test
switches.** Suitable for harsh environments.
Supplied with an internal switches for testing
Fire and Fault, 1 x M12 cable gland. IP66.
Dimensions 75 x 80 x 57 mm



**53106-013 316 Stainless Steel EOL unit with external
key switch.** Suitable for harsh environments.
Supplied with an external key switch for
testing Fire and Fault, 1 x M12 cable gland.
IP65. Dimensions 126 126 x 80mm



53106-014 ABS EOL unit with external key switch.
Supplied with an external key switch for
testing Fire and Fault, 1 x PG 7 cable gland.
IP66. Dimensions 120 x 120 x 80 mm



End Of Line Units & Junction Boxes

Pt Number	Junction Boxes
-----------	----------------

53102-001	Junction Box LHD Field wiring to LHD Polycarbonate (PC) box. IP66, Supplied with 1 x PG 7, 1 x M20 cable glands. Dimensions 120 x 80 x 57 mm
-----------	--

53102-011	Junction Box LHD Through connection. Polycarbonate (PC) box. IP66, Supplied with 2 x PG 7, glands. Dimensions 120 x 80 x 57 mm
-----------	--

53102-003	Junction Box LHD Field wiring to LHD 316 Stainless box, IP 65 Supplied with 1 x M12, 1 x M16 cable glands. Dimensions 126 x 126 x 80 mm.
-----------	--

53102-013	Junction Box LHD Through connection. 316 Stainless Steel box. IP65 Supplied with 2 x M12 cable glands. Dimensions 126 x 126 x 80mm
-----------	--

53102-023	Junction Box LHD Cable in & LHD Through connection. 316 Stainless Steel box. IP65 Supplied with 2 x M12, 1 x M16 cable glands. Dimensions 126 x 126 x 80mm
-----------	--

